



91 IN 1

A unique PTFE based fast acting, multi-purpose penetrant and lubricant.



Features & Benefits

- Multi-Purpose product with 90 plus uses - one product does it all
- A jack of all trades and a master of many as it lubricates, penetrates and displaces moisture - less inventory, saving money and waste
- Contains PTFE - will not evaporate or freeze
- 360° spray valve and associated second nozzle with 150 mm straw - allows the can to be sprayed in any direction making hard to reach areas accessible
- Leaves a lubricating coating - protects against dirt, salt and water
- Outstanding capillary action - allows it to penetrate fine tolerances to lubricate and protect
- Free of silicone, acid and resin - does not harm painted surfaces or plastics and suitable for lock cylinders

P/N	Product	S/C	Packaging
83676	91 IN 1	IN1	500 ml aerosol with 150mm extension straw with nozzle

Application

91 IN 1 has been formulated as a unique PTFE based fast acting penetrant and lubricant with over 90 different uses, for example freeing seized corroded parts, lubricating and protecting of tools, cables, electric switch gear with applications in vehicles, cycles, agriculture, industry, marine, sports and leisure. Simply put, it protects, prevents, cleans, dissolves, eases, shines, lubricates, penetrates, loosens, frees, removes, quietens, eliminates, stops, unsticks etc.

N.B.: 91 IN 1 should not be applied to live mains voltage.

Instructions

1. Shake well before use.
2. Apply 91 IN 1 liberally and allow to penetrate for a short period.
3. For best results do not wipe off as the solvent will evaporate leaving a protective, lubricating film.

N.B.: If necessary, remove excess corrosion from parts. Heavily rusted parts may need a second application.



Technical Information

Base:	PTFE based lubricant
Consistency:	Slightly oily liquid
Colour:	Pale amber
Shelf life:	60 months
Custom tariff code:	3403 1910
VOC:	595 g/l

Specific gravity (20 °C):	0.820 g/ml 20 °C
Temperature range:	-15 °C to +50 °C
Temporary:	Not determined
Film Weight:	2 gm ²
Flash Point:	Aerosol 45 °C, product as liquid 81 °C



SDS available on www.kenteurope.com

Terms and Conditions

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of KENT (United Kingdom) Ltd. This data sheet and its contents (the "Information") belong to the KENT (United Kingdom) Ltd. or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including

liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. KENT is the trading name of KENT (United Kingdom) Ltd.

Registered Office: Amber House,
Showground Road, Bridgewater, Somerset, United Kingdom TA6 6AJ
All rights reserved.

KENT (United Kingdom) Ltd, Forsyth House, Pitreavie Drive, Pitreavie Business Park, Dunfermline, Fife KY11 8US Tel : 0800 136925 or 01383 723344 between 08:30-17:30
Monday-Thursday, 09:00-15:00 on Fridays'. For out of hours queries please Fax us on 01383 735829 or Email: kentinfo.uk@kenteurope.com

REV: 24/03/2016