

SL500 / SL85

KENT

UPDATED: 20.05.2015



A fast acting, penetrating grease for lubrication of general moving components subjected to high pressure, impact and vibration.

P/N°: SL500

• 84339 11

• 84339 21

• 84339 45

S/C: KSL
P/N°: SL85

• 83688 11

S/C: KSL85

Features & Benefits

Special formulation: • Thin while spraying ► good penetration.
• Thick after “flash off” ► good protection and lubrication.

- Excellent penetrant - Gets to where lubricant is required.
- Transparent appearance - Invisible protection.
- Moisture repellent - Protects against corrosion.
- High adhesion - Stays where it is needed.
- High lubricity - Reduces wear and friction.

Applications

SL500 / SL85 is a lubricant based on a mixture of synthetic oil, mineral oil, tackifiers, anti wear-, anti oxidation-, anti corrosion additives and PTFE.

It's a spray grease with excellent penetrating ability and very high adhesion and designed for lubricating general moving components during the service schedule, such as:

Door hinges, check straps, door locks, bonnet and boot hinges and catches, pedal pivots, fuel cap locks, seat rails, control linkages, cables, chains (O/X/Z-ring) and much more.

Once the propellant has flashed off, it leaves a high degree of both protection and lubricating properties.

Instructions

1. Shake well before use.
2. Clean the moving parts before application with a KENT degreaser (e.g. Soft Surface Cleaner or Acrysol) and dry with a cloth.
3. Spray from a short distance directly onto the moving parts of the component requiring lubricating.
4. Allow the product to flow and let the solvents evaporate.
5. Remove excess of lubrication.

DS118

Hints & Tips



Certificate No. 1427
ISO 9001:2008

SL500 / SL85

Technical Information

Appearance: Yellow/Clear - Gel Like Liquid

Odour: Negligible

Accessoires: 10 mm Spraypipe (SL500)

Packaging: SL500 = 500 ml Aerosol

SL85 = 85 ml Aerosol

Customs Tariff Code: 3403 19 19

Shelf Life: 30 Months

SDS: Yes

Timken OK Load (ASTM D 2782): > 50

4-Ball Welding (DIN 51350):

Part 2: EP: 1500 rpm, OK Load: 2200 N, Welding Load: 2300 N

Part 3: Anti-Wear: Scar Diameter / 1500rpm / 1 h / 200N: 0,30

Water Separation/Demulsifying (ASTM D 1401): 40-40-0

Copper Corrosion (ASTM D 1300): 3h / 100 °C: 1-b

Application Temp.: 10 to 35 °C

Temp Resistance: -35 to 200 °C

Density (20°C): 0.687 g/ml

Corrosion ASTM D 665:

Part A: Distilled Water: No corrosion

Part B: Sea Water: No corrosion

In order to provide you with the most appropriate Personal Protective Equipment when using our products, KENT advises that you follow the guidelines on the packaging of the product before use. The guidelines are there for your protection and KENT provides a range of Personal Protection Equipment such as clothing, eye glasses, goggles, face shields and breathing apparatus, complying with the latest European legislation. If you require further advice then please phone our freephone number and we will be pleased to help you.
Telephone: 0800 / 136925

Terms and Conditions

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of KENT UK. This data sheet and its contents (the "Information") belong to KENT UK or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the business assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including

liability resulting from negligence or where the business was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the business liability for death or personal injury resulting from its negligence.

Registered Office: Amber House, Showground Road, Bridgwater, Somerset, United Kingdom TA6 6AJ
All rights reserved.

Process Centre: KENT UK, Pitreavie Crescent, Pitreavie Business Park, Dunfermline Fife KY11 8UQ
T: Freephone 0800 / 136 925 between 08:30 - 17:30 Monday - Thursday, 09:00 - 15:00 on Fridays.
For out of hours queries please Fax us on 01383 / 735829 or Email: KENTsales.UK@kenturope.com