


Logo Tape

Logo Tape is specially designed for recovering logos and emblems from all types of vehicles. It is also ideal for positioning parts before final fixing or for fixing decorative and promotional items.



Features & Benefits

- Self cutting adhesive layer Transfer of the adhesive layer without messy stringing
- High tack High immediate adhesion
- Large dimensions Ideal for large emblems
- Time -and cost-efficient Allows reclaiming the badges and decals

| P/N | Product | S/C | Packaging |
|-------|-----------|------|---------------------------|
| 86687 | Logo Tape | KLT2 | 10 sheets (10 cm x 20 cm) |

Application

Logo Tape allows you to bond lightweight logos and complex shapes on smooth and hard surfaces.

For Automotive and Marine:

· Decorative trims, badges, logos and decals

For building maintenance:

- · Attaching lightweight signs, nameplates and plaques
- · Mounting prints and photographs

Instructions

- 1. Use KENT Soft Surface Cleaner to clean the area where the badge is to be applied on.
- 2. Peel the backing strip off to expose the adhesive layer.
- 3. Place the badge onto the adhesive layer. Apply pressure evenly over the badge.
- 4. Lift the badge off the paper taking the adhesive with it.
- 5. Apply the badge to the desired area. Ensure that the badge is in the correct position. The more pressure that is applied during application of the tape, the better the bond.

Hint: When removing logos from a vehicle, make sure the original foam backing stays intact for better adhesion. Apply KENT Masking Tape on top of decals and on the vehicle for an easier application.



Technical Information

| Carrier: | Silicone release liner |
|---------------------|--------------------------------------|
| Adhesive layer: | Acrylic |
| Colour: | Clear |
| Length: | 20 cm |
| Width: | 10 cm |
| Thickness: | Adhesive layer 0.04 mm (+/- 0.05 mm) |
| Shelf life: | 12 months |
| Custom tariff code: | 39191012 |
| VOC: | 0 g/l |
| | |
| Adhesive strength: | 8.75 N/100 mm (on steel) |

| Holding power: | 0.1 mm/30 minutes |
|--------------------------|-------------------|
| Application temperature: | -10 to 35°C |
| Service temperature: | -40 to 170°C |



SDS available on www.kenteurope.com

Terms and Conditions

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of KENT (United Kingdom) Ltd This data sheet and its contents (the "Information") belong to KENT (United Kingdom) Ltd, or are licensed to it. No license is granted for the use of it other than for information purposes in connection with he products to which it relates. No license of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility To resource or be accurate out the Group as curves on the sports of the Group's fability for death or personal injur for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for hemselves the information and he suitability of the products for heir purpose and nor make any assumptions based on information included or amitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including the including the incline the including the including the including the i

liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence KENT is the trading name of KENT (United Kingdom) Ltd.

All rights reserved

KENT (United Kingdom) Ltd, Forsyth House, Pitreavie Drive, Pitreavie Business Park, Dunfermline, Fife KY11 8US Tel: 0800 136925 or 01383 723344 between 08:30-17:30 Monday-Thursday, 09:00-15:00 on Fridays'. For out of hours queries please Fax us on 01383 735829 or Email: KENTsales.UK@kenteurope.com