

Air Co Refresh

UPDATED: 02.02.2015



Part N°: 85788 (ACC)
Fruits of the Forest - 300ml



Part N°: 86089 (ACE)
Eucalyptus - 300ml

A high performance product for use with all air conditioning units. The unique clinging foam action ensures fast, effective refreshing of all evaporator systems and ductwork. The use of low odour solvents ensures that the vehicle can be returned to the customer in the shortest possible time.

Features

- Convenient aerosol application system
- Unique long lasting foaming action
- 1M extension wand for use in long ductwork
- Contains no ethyl alcohol
- Low odor solvents

Benefits

- Easy to apply
- Ensures fast effective use
- Allows directing of the product into hard to reach systems
- Ensures the vehicle can be returned quickly
- No residual smells

Applications

Air conditioning units are becoming more common place on today's vehicles, and this trend is set to increase in coming years.

The major disadvantage of Air Con Systems is that if they are not maintained, particularly around the evaporator, deposits will quickly collect. Air Co Refresh is designed to spray a clinging foam, via the extension nozzle, direct into the heart of the system, and then the foam will revert to liquid and then drain away via the drain tubes.

In order to achieve the best results from the Air Co Refresh, it is important that the evaporator unit itself is precisely targeted.

This may involve the removal of ductwork, pollen filters and other components in the system. Due to the widely varying design of heater matrices and air conditioning systems, it can sometimes be difficult for the non-specialist to identify the exact position of all the components. However, all the systems work on an identical principle, it is purely a question of tracing them and making use of the skills of the mechanic, who will have needed to remove many of these components during normal servicing.

Because of the obvious difficulties involved in removing ductwork, pollen filters, etc. we have successfully sourced a 1m extension tube which should overcome a lot of these problems. The wand is inserted in a convenient aperture near the outer face of the evaporator. Or application holes could be drilled, taking care not to damage any components. Spray the product whilst moving the tube in a circular motion. This can be performed before or whilst the fan is turned on. Any application holes drilled must be plugged. The action of the fan draws the foam liquid onto the evaporator.

Instructions for use:

- Shake well before use.
- Apply the foam as close as possible to the evaporator. This can be done through the outlet of the evaporator.
- Bring the nozzle of the spray tube close to or against the evaporator.
- Depending on the size of the system to be treated, use a maximum of 1 spray can.
- Allow at least 15 minutes for the product to take effect
- Switch the fan to at slow speed for 5 minutes.



Hints & Tips





Air Co Refresh

Technical Information



Part N°:	85788, 86089	Consistency:	White foam
Description:	Air Co Refresh, 300ml	Application:	Easy spray aerosol supplied with 1M extension tube
Shelf Life:	24 months	Removal:	Applied to evaporator wait for product to break down and pull off dirt
Selling Unit:	EA	Breaking of Foam:	5 mins
Hazard info:	Extremely Flammable	Odour:	Pleasant fruity odour – Eucalyptus odour
VOC:	116g/L	Set of 5 extension straws:	86236 00
Stock Code:	ACC / ACE		
Customs Tariff Code:	34029090		
SDS:	Yes		

Associated Products Re-Odouriser II, Air co one shot, Protective clothing/gloves, New APFC, Wiper roll

Market Segments



Health & Safety Information – see safety data sheet

AEROSOL WARNINGS

Warning: Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep out of the reach of children

In order to provide you with the most appropriate Personal Protective Equipment when using our products, KENT advises that you follow the guidelines on the packaging of the product before use. The guidelines are there for your protection and KENT provides a range of Personal Protection Equipment such as clothing, eye glasses, goggles, face shields and breathing apparatus, complying with the latest European legislation. If you require further advice then please phone our freephone number and we will be pleased to help you. Telephone: 08 00 136925

Terms and Conditions

No part of this publication may be reproduced transmitted or stored, electronically, mechanically or photocopied without the prior permission of KENT UK. This data sheet and its contents (the "Information") belong to KENT UK or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied.

The Information supplied is believed to be accurate but the business assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including

liability resulting from negligence or where the business was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the business liability for death or personal injury resulting from its negligence.

Registered Office: Amber House, Showground Road, Bridgewater, Somerset, United Kingdom TA6 6AJ

All rights reserved.

KENT Ltd. KENT UK, Pitreavie Crescent, Pitreavie Business Park, Dunfermline Fife KY11 8UQ : Freephone 0800 136925 or 01383 737172 between 08:30-17:00. For out of hours queries please Fax us on 01383 735829 or **Email:** KENTsales.UK@kenturope.com

DS64