



Aerosol Spray Paints



CREATED: 12.08.15



A range of General Purpose Acrylic based paints

- 86243 33** Gloss Black
- 86244 33** Satin Black
- 86245 33** Matt Black
- 86246 33** Gloss White

Features

- Excellent covering power
- Excellent durability
- Excellent resistance to sunlight and colour fade
- Excellent adhesion to primed surfaces

Benefits

- Spray can cover large area – cost efficient
- Good resistance to wear – long life
- Does not require touch up due to effects of fading
- Good consistent surface coating

Applications

Can be used on all types of metals and rigid plastic surfaces when used in conjunction with the appropriate primers.

On surfaces treated with unknown primers, or if the use of a primer isn't certain, it is advised to trial a test panel first.

Prepare the primed surface to be treated, ensuring freedom from dust, grime, greases, oils, etc.; use Acrysol or similar cleaner and dry thoroughly.
If the primed surface needs flattening, use 1200 grade abrasive paper and then clean as above.

Instructions

1. Shake the can thoroughly for at least two minutes. Repeat shaking at regular intervals during use.
2. Apply lightly from a distance of 20-25 cm. Apply 2 to 3 light coats to achieve coverage. Leave 10 to 15 minutes drying between coats.
3. Allow to fully harden for at least 24 hours after application of final coating.
4. On completion of use, invert can and depress actuator for a few seconds to clear the nozzle.

DS649

Hints & Tips

Use Acrysol to thoroughly clean surfaces before priming or spray application



Certificate No. 1427/97

Certificate No. 1427/97

Aerosol Spray Paints



Technical Information

Part number: 86243 Gloss Black GBSP	Volume	500ml
86244 Satin Black SBSP		
86245 Matt Black MBSP	Customs Tariff Code:	3208 90 91
86246 Gloss White WSP		
	SDS:	Yes
Shelf life: 24 Months	VOC:	GB 651g/l; SB 656g/l
		MB 652g/l; GW 621g/l
Selling Unit: Each		
Packaging: 500ml Aerosol	Specific Gravity:	0.94 to 1.09 g/ml
Label codes: 33	Viscosity:	up to 1,500 cPs
Service Temperature: up to 80°C	Application Temperature:	15 to 25°C
Colour:		
Black = RAL 9005 (same shade, various degrees of gloss)		
White = RAL 9003		

In order to provide you with the most appropriate Personal Protective Equipment when using our products, KENT advises that you follow the guidelines on the packaging of the product before use. The guidelines are there for your protection and KENT provides a range of Personal Protection Equipment such as clothing, eye glasses, goggles, face shields and breathing apparatus, complying with the latest European legislation. If you require further advice then please phone our freephone number and we will be pleased to help you. Telephone: 0800 136925

Terms and Conditions

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of KENT UK.

This data sheet and its contents (the "Information") belong to KENT UK or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the business assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including

liability resulting from negligence or where the business was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the business liability for death or personal injury resulting from its negligence.

Registered Office: Amber House, Showground Road, Bridgwater, Somerset, United Kingdom TA6 6AJ
All rights reserved.

Process Centre: KENT UK, Pitreavie Crescent, Pitreavie Business Park, Dunfermline
Fife KY11 8UQ Tel : Freephone 0800 136925 or 01383 737393 between 08:30-17:30
Monday-Thursday, 09:00-15:00 on Fridays. For out of hours queries please Fax us on
01383 735829 or Email: KENTsales.UK@kent europe.com

DS649